

Electrically Conductive Rubber Plate Swivel Castor Brake 125mm 100kg

Product code: SSM125GRECSWB

Grade 304 Stainless steel swivel castor with a top plate fixing fitted with a grey electrically conductive tyre on a black polypropylene centred wheel with plain bore and a total lock brake. Wheel diameter 125mm, tread width 32mm, overall height 156mm, top plate 90mm x 70mm, hole centres 75mm x 56mm or 64mm x 44mm. Load capacity 100kg. Conductive offers a resistance $R < 10 \Omega$



Diameter (mm)	125
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	156
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Plain
Tread (mm)	32
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	8
Load Capacity (kg)	100
Temperature Resistance	-15 °C TO +80 °C
Plate Size (mm)	90 x 70
Hole Centres (mm)	75/64 x 56/44
Top Plate Thickness (mm)	2
Swivel Radius (mm)	107

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

