

Electrically Conductive Rubber Plate Swivel Castor 125mm 80kg Load

Product code: SSRA125GREC

Grade 304 Pressed stainless steel swivel castor with a flate plate fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bore. Wheel diameter 125mm, tread width 24mm, overall height 149mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5mm x 42.5mm Load capacity 80kg. Conductive offers a resistance $R < 10 \Omega$



Diameter (mm)	125
Fixing Option	Plate
Castor Type	Swivel
Height (mm)	149
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Plain
Tread (mm)	24
Fork Thickness (mm)	1.8
To Suit Fixing Bolt (mm)	6
Load Capacity (kg)	80
Temperature Resistance	-15 °C TO +80 °C
Plate Size (mm)	60 x 60
Hole Centres (mm)	49/43 x 49/43
Top Plate Thickness (mm)	1.8
Swivel Radius (mm)	106

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

